

■Feature

- ◆Aluminium alloy structure, easy to radiate heat
- ◆High strength shock-resistance capability
- ◆High resolution picture quality
- ◆Motion detection recording
- ◆Motion detection with sensitivity & area settings
- ◆With auto record function
- ◆One removable HDD tray, supports up to 500GB HDD
- ◆With power output function to supply cameras
- ◆With auto-switch display function
- ◆Password protection
- ◆Built-in USB2.0 port for video backup to computer
- ◆With IR remote control
- ◆Self-recovery after power reconnected

■Picture**■Specifications**

Model	MNT-D4104
Video Compression	M-JPEG (12-20K bytes/frame)
Video System	NTSC / PAL
Operation System	Stand-alone
Video Input	BNC 4-channel
Video Output	BNC 1-channel
Display Frame Rate	NTSC: 120 fps / PAL: 100 fps
Recording Frame Rate	NTSC: Max. 30 fps / PAL: Max. 25 fps
Display Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Record Resolution	NTSC: 320 x 112, 640 x 224 / PAL: 320 x 136, 640 x 272
Record Mode	Continuous / time schedule / motion detection
Display Mode	Each, Quad, Auto-switch
HDD Interface	One removable HDD tray, supports up to 500GB HDD
Estimated Record Length	250GB Hard drive @ 25fps @ Normal Quality (250x1024x1024 K byte) / (25x15x60x 60) = 194 Hours
Playback Search	Time & Date, Event List
Power Output	DC12V / 800mA, supplies to cameras
USB	For PC playback & backup / USB 2.0
Remote Control	Included
Working Temperature	-5°C~50°C/20~80%
Storage Temperature	-20°C~50°C/20~95%
Power Supply	DC7V~36V
Dimension	250mm(D) x 130mm(W) x 125mm(H)